

ecostore
Refrigerated
Cabinets




 Electrolux



Thinking of you
Electrolux

ecostore Premium:

the next generation of advanced digital electronics



Capacity

- ▶ **50 litres more** available space
Unbeatable storage capacity in a compact footprint
- ▶ **Maximum recovery of internal space**, thanks to **hidden evaporator** and new component layout
- ▶ **44 grid level positions** for **increased loading capacity**

Cleanability

- ▶ **Water-safe design** and **rounded corners** for fast and **easy cleaning** operations
- ▶ **Internal components** (air conveyors, runners, supports and grids) are **fully removable without tools**
- ▶ Easily **removable** “balloon” profiled magnetic **door gasket** for **maximum hygiene**

ecostore Touch:
innovative touch screen
for worry-free control



Efficiency

- ▶ Highly **efficient components**, 75mm thick **cyclopentane insulation** and removable “balloon” **gasket with triple insulation area**
- ▶ **Frost Watch Control⁴** intelligent defrost **saves energy** by defrosting only when necessary
- ▶ **R290 natural refrigerant gas reduces energy consumption** and extends the life of the compressor



Performance


- ▶ **Optiflow:** the intelligent air circulation system which **adapts to your load** for the **best cooling results**
- ▶ **Removable** air conveyors with innovative design provide **excellent** and **fast air distribution**
- ▶ **Fast temperature recovery** and **humidity control** guarantee the **highest quality** and the **best food preservation**



- ▶ **Wire-frame condenser**
Clean-free to guarantee high performances at all times




- ▶ **LCD Touch screen**
Innovative touch display for easy and clear operation




- **Frontal door lock**
provides additional security



- ▶ **Optiflow**
Vertical and horizontal air circulation for **optimal temperature uniformity**



- ▶ **Innovative air conveyors**
provide excellent and **fast air distribution** and are **fully removable** to facilitate cleaning



- **Rounded corners and removable stainless steel runners and supports** facilitate cleaning of internal chamber



- **Maximum stability and flexibility**
Can be mounted on stainless steel feet, swivelling wheels, concrete plinth or marine feet

■ Standard feature on all models





High efficiency components

Low energy compressors,
high surface evaporator
and high efficiency fans



Hidden evaporator

For maximum internal capacity



Internal LED light

The lowest energy consumption
(internal neon light on glass
door models)



IPX5 water protection

Full frontal water-proof design



75mm insulated walls
and the improved gasket design
assure **low energy consumption**



Removable
wide “balloon” profiled **gasket**,
with triple insulation area,
provides an **excellent seal** thus
reducing heat dispersion



Included feature on selected models

ecostore Touch



1 full door



2 full doors

Gross capacity - lt	670	1430
LCD Touch screen display	•	•
Advanced digital display		
Internal light	LED	LED
Operating temperature at 43 °C	-2/+10 °C or -15/-22 °C	-2/+10 °C or -15/-22 °C
Dual temp. operation at 43 °C	n.a.	n.a.
Remote cooling unit		
Refrigerant	R134a/R404a/R290	R134a/R404a/R290
Cyclopentane insulation	•	•
Defrost type	Frost Watch Control [†]	Frost Watch Control [†]
External and internal panels in AISI	304	304
UK version with Schuko plug and wheels		
External dimensions - mm (wxdxh)	710x837x2050	1441x837x2050

ecostore Premium



1 full door



2 full doors



2 - 1/2 doors

Gross capacity - lt	670	1430	670
LCD Touch screen display	•	•	•
Advanced digital display			
Internal light	LED	LED	LED
Operating temperature at 43 °C	-2/+10 °C or -15/-22 °C	-2/+10 °C or -15/-22 °C	-2/+10 °C or -15/-22 °C
Dual temp. operation at 43 °C	n.a.	-2/-2 °C or -2/-22 °C	-2/-2 °C or -2/-22 °C
Remote cooling unit	•	•	•
Refrigerant	R134a/R404a/R290	R134a/R404a/R290	R134a/R404a/R290
Cyclopentane insulation	•	•	•
Defrost type	Frost Watch Control	Frost Watch Control	Frost Watch Control
External and internal panels in AISI	304	304	304
UK version with Schuko plug and wheels	•	•	•
External dimensions - mm (wxdxh)	710x837x2050	1441x837x2050	710x837x2050

ecostore Premium



1 full door &
2 - 1/2 doors



4 - 1/2 door



1 glass door



2 glass doors

Gross capacity - lt	1430	1430	670	1430
LCD Touch screen display	•	•	•	•
Advanced digital display				
Internal light	LED	LED	LED and NEON	LED and NEON
Operating temperature at 43 °C	n.a.	-2/+10 °C or -15/-22 °C	+2/+10 °C or -15/-20 °C (at 32 °C)	+2/+10 °C or -15/-20 °C (at 32 °C)
Dual temp. operation at 43 °C	-2/-22 °C or -2/-6 °C (Fish)	n.a.	n.a.	n.a.
Remote cooling unit				
Refrigerant	R134a/R404a/R290	R134a/R404a/R290	R134a/R404a/R290	R134a/R404a/R290
Cyclopentane insulation	•	•	•	•
Defrost type	Frost Watch Control	Frost Watch Control	Frost Watch Control	Frost Watch Control
External and internal panels in AISI	304	304	304	304
UK version with Schuko plug and wheels			•	•
External dimensions - mm (wxdxh)	1441x837x2050	1441x837x2050	710x837x2050	1441x837x2050