

SkyLine PremiumS Natural Gas Combi Oven 10GN1/1

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


217792 (ECOG101T2G1)

SkyLine PremiumS combi boiler oven with touch screen control, 10x1/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, boiler in AISI 316

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Double glass door with LED lights
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C - 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C - 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C - 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 Steam cycle (100 °C): seafood and vegetables.
 High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles+:
 - Regeneration (ideal for banqueting on plate or rethermalizing on tray),
 - Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
 - Proving cycle,
 - EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
 - Sous-vide cooking,
 - Static Combi (to reproduce traditional cooking from static oven),
 - Pasteurization of pasta,
 - Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood),
 - Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
 - Advanced Food Safe Control (to drive the cooking with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- OptiFlow air distribution system to achieve

APPROVAL: _____

maximum performance in cooking evenness and temperature control thanks to a special design of the cooking chamber combined with high precision variable speed fan and venting valve.

- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Pictures upload for full customization of cooking cycles.
- Automatic fast cool down and pre-heat function.
- Reduced power function for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- 3 different chemical options available: solid, liquid (requires optional accessory), enzymatic.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (SkyDuo Kit available as optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Automatic consumption visualization at the end of the cycle.

Construction

- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler (Registered Design at EPO).
- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.


- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Optional Accessories


- Water softener with cartridge and flow meter for 6 & 10 GN 1/1 ovens (low-medium steam usage - less than 2hrs per day full steam) PNC 920002
- Water softener with cartridge and flow meter (high steam usage) PNC 920003
- Water softener with salt for ovens with automatic regeneration of resin PNC 921305
- Resin sanitizer for water softener (921305) PNC 921306
- Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) PNC 922003
- Pair of AISI 304 stainless steel grids, GN 1/1 PNC 922017
- Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 PNC 922036
- AISI 304 stainless steel grid, GN 1/1 PNC 922062
- Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 PNC 922086
- External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) PNC 922171
- Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm PNC 922189
- Baking tray with 4 edges in perforated aluminum, 400x600x20mm PNC 922190
- Baking tray with 4 edges in aluminum, 400x600x20mm PNC 922191
- Pair of frying baskets PNC 922239
- AISI 304 stainless steel bakery/pastry grid 400x600mm PNC 922264
- Double-step door opening kit PNC 922265
- Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 PNC 922266
- USB probe for sous-vide cooking PNC 922281
- Grease collection tray, GN 1/1, H=100 mm PNC 922321
- Kit universal skewer rack and 4 long skewers for Lenghtwise ovens PNC 922324
- Universal skewer rack PNC 922326
- 4 long skewers PNC 922327
- Water nanofilter for 6 & 10 GN 1/1 ovens PNC 922342
- External reverse osmosis filter for 6 & 10 GN 1/1 ovens PNC 922343
- Multipurpose hook PNC 922348
- 4 flanged feet for 6 & 10 GN , 2", 100-130mm PNC 922351
- Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 PNC 922362
- Thermal cover for 10 GN 1/1 oven and blast chiller freezer PNC 922364
- Tray support for 6 & 10 GN 1/1 disassembled open base PNC 922382
- Wall mounted detergent tank holder PNC 922386
- Tray rack with wheels 10 GN 1/1, 65mm pitch PNC 922601
- Tray rack with wheels, 8 GN 1/1, 80mm pitch PNC 922602

- | | |
|--|--|
| <ul style="list-style-type: none"> • Bakery/pastry tray rack with wheels holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners) PNC 922608
<input type="checkbox"/> • Slide-in rack with handle for 6 & 10 GN 1/1 oven PNC 922610
<input type="checkbox"/> • Open base with tray support for 6 & 10 GN 1/1 oven PNC 922612
<input type="checkbox"/> • Cupboard base with tray support for 6 & 10 GN 1/1 oven PNC 922614
<input type="checkbox"/> • Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or 400x600mm PNC 922615
<input type="checkbox"/> • External connection kit for liquid detergent and rinse aid PNC 922618
<input type="checkbox"/> • Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device and drain) PNC 922619
<input type="checkbox"/> • Stacking kit for gas 6 GN 1/1 oven placed on gas 10 GN 1/1 oven PNC 922623
<input type="checkbox"/> • Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer PNC 922626
<input type="checkbox"/> • Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens PNC 922630
<input type="checkbox"/> • Stainless steel drain kit for 6 & 10 GN oven, dia=50mm PNC 922636
<input type="checkbox"/> • Plastic drain kit for 6 & 10 GN oven, dia=50mm PNC 922637
<input type="checkbox"/> • Grease collection kit for open base (trolley with 2 tanks, open/close device and drain) PNC 922639
<input type="checkbox"/> • Wall support for 10 GN 1/1 oven PNC 922645
<input type="checkbox"/> • Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast chiller freezer, 65mm pitch PNC 922648
<input type="checkbox"/> • Banquet rack with wheels 23 plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch PNC 922649
<input type="checkbox"/> • Dehydration tray, GN 1/1, H=20mm PNC 922651
<input type="checkbox"/> • Flat dehydration tray, GN 1/1 PNC 922652
<input type="checkbox"/> • Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382 PNC 922653
<input type="checkbox"/> • Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and 80mm pitch PNC 922656
<input type="checkbox"/> • Stacking kit for gas 6 GN 1/1 oven placed on 7kg and 15kg crosswise blast chiller freezer PNC 922657
<input type="checkbox"/> • Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1 PNC 922661
<input type="checkbox"/> • Heat shield for 10 GN 1/1 oven PNC 922663
<input type="checkbox"/> • Kit to convert from natural gas to LPG PNC 922670
<input type="checkbox"/> • Kit to convert from LPG to natural gas PNC 922671
<input type="checkbox"/> • Flue condenser for gas oven PNC 922678
<input type="checkbox"/> • Fixed tray rack for 10 GN 1/1 and 400x600mm grids PNC 922685
<input type="checkbox"/> • Kit to fix oven to the wall PNC 922687
<input type="checkbox"/> | <ul style="list-style-type: none"> • Tray support for 6 & 10 GN 1/1 oven base (not for the disassembled one) PNC 922690
<input type="checkbox"/> • 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm PNC 922693
<input type="checkbox"/> • Reinforced tray rack with wheels, lowest support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch PNC 922694
<input type="checkbox"/> • Detergent tank holder for open base PNC 922699
<input type="checkbox"/> • Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base (not for the disassembled one) PNC 922702
<input type="checkbox"/> • Wheels for stacked ovens PNC 922704
<input type="checkbox"/> • Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens PNC 922709
<input type="checkbox"/> • Mesh grilling grid, GN 1/1 PNC 922713
<input type="checkbox"/> • Probe holder for liquids PNC 922714
<input type="checkbox"/> • Exhaust hood with fan for 6 & 10 GN 1/1 ovens PNC 922728
<input type="checkbox"/> • Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens PNC 922732
<input type="checkbox"/> • Exhaust hood without fan for 6&10 1/1GN ovens PNC 922733
<input type="checkbox"/> • Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens PNC 922737
<input type="checkbox"/> • Fixed tray rack, 8 GN 1/1, 85mm pitch PNC 922741
<input type="checkbox"/> • Fixed tray rack, 8 GN 2/1, 85mm pitch PNC 922742
<input type="checkbox"/> • 4 high adjustable feet for 6 & 10 GN ovens, 230-290mm PNC 922745
<input type="checkbox"/> • Tray for traditional static cooking, H=100mm PNC 922746
<input type="checkbox"/> • Double-face griddle, one side ribbed and one side smooth, 400x600mm PNC 922747
<input type="checkbox"/> • Trolley for grease collection kit PNC 922752
<input type="checkbox"/> • PRESSURE REDUCER PNC 922773
<input type="checkbox"/> • Non-stick universal pan, GN 1/1, H=20mm PNC 925000
<input type="checkbox"/> • Non-stick universal pan, GN 1/1, H=40mm PNC 925001
<input type="checkbox"/> • Non-stick universal pan, GN 1/1, H=60mm PNC 925002
<input type="checkbox"/> • Double-face griddle, one side ribbed and one side smooth, GN 1/1 PNC 925003
<input type="checkbox"/> • Aluminum grill, GN 1/1 PNC 925004
<input type="checkbox"/> • Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 PNC 925005
<input type="checkbox"/> • Flat baking tray with 2 edges, GN 1/1 PNC 925006
<input type="checkbox"/> • Baking tray for 4 baguettes, GN 1/1 PNC 925007
<input type="checkbox"/> • Potato baker for 28 potatoes, GN 1/1 PNC 925008
<input type="checkbox"/> • Non-stick universal pan, GN 1/2, H=20mm PNC 925009
<input type="checkbox"/> • Non-stick universal pan, GN 1/2, H=40mm PNC 925010
<input type="checkbox"/> • Non-stick universal pan, GN 1/2, H=60mm PNC 925011
<input type="checkbox"/> • Wood chips: oak, 450gr PNC 930209
<input type="checkbox"/> • Wood chips: hickory, 450gr PNC 930210
<input type="checkbox"/> • Wood chips: maple, 450gr PNC 930211
<input type="checkbox"/> • Wood chips: cherry, 450gr PNC 930212
<input type="checkbox"/> • Compatibility kit for installation on previous base GN 1/1 PNC 930217
<input type="checkbox"/> |
|--|--|

Front




Side



- | | |
|---------------------------|-------------------------------|
| CWI1 = Cold Water inlet 1 | EI = Electrical inlet (power) |
| CWI2 = Cold Water Inlet 2 | G = Gas connection |
| D = Drain | |
| DO = Overflow drain pipe | |

Top



Electric

Supply voltage:
 217792 (ECO10IT2G1) 220-240 V/1 ph/50 Hz
 Electrical power, default: 1.1 kW
 Circuit breaker required

Gas

Gas Power: 31 kW
 Standard gas delivery: Natural Gas G20
 ISO 7/1 gas connection diameter: 1/2" MNPT
 LPG:
 Total thermal load: 124538 BTU (31 kW)

Water:

Water inlet connections "CWI1-CWI2": 3/4"
 Pressure, bar min/max: 1-4.5 bar
 Drain "D": 50mm
 Max inlet water supply temperature: 30 °C
 Chlorides: <20 ppm
 Conductivity: >285 µS/cm
 Electrolux recommends the use of treated water, based on testing of specific water conditions.
 Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right hand sides.
 Suggested clearance for service access: 50 cm left hand side.

Capacity:

Trays type: 10 - 1/1 Gastronorm
 Max load capacity: 50 kg

Key Information:

Door hinges: Right Side
 External dimensions, Width: 867 mm
 External dimensions, Height: 1058 mm
 External dimensions, Depth: 775 mm
 Weight: 153 kg
 Net weight: 153 kg
 Shipping weight: 168 kg
 Shipping volume: 1.04 m³